

DENSO RE-INSTATEMENT TAPE

Seam Seal Mastic

Description

Denso Re-instatement Tape is a cold applied polymer modified bituminous strip for sealing joints between existing asphalt and new asphalt installations. It is produced in rolls with a disposable release liner and used in conjunction with Denso Primer D.

Uses

Used as a waterproofing joint sealant where new asphalt patches or maintenance is required, against existing asphalt surfaces. It also seals joints between asphalt and concrete or steel, such as concrete curb work or catch basin or manhole covers.

Features

- Cold applied compound in dispensable tape form
- 100% coverage of the perimeter of the joint
- Uniform 0.08" (2 mm) seal
- Minimum delay in road closing
- High adhesion to asphalt, concrete and steel
- Tough, durable, long-life
- Prevents ingress of water into joint

Application

Clean and dry the horizontal edge surface of the joint. Apply Denso Primer D to the horizontal edge to be sealed, using a brush or roller. Allow the primer to dry to a tack consistency. Apply the tape to the horizontal edge of the existing asphalt, to a width of approximately 0.59" (15 mm), allowing the remaining width of tape to fall down into position in the open cut area. Apply new asphalt to the joint face and open cut area.



Denso Re-instatement Tape

Property Specifications

PROPERTIES	English	Metric
S.G. @ 68°F (20°C)	1.0	1.0
Softening Point	194 to 212°F	90 to 100°C
Resistance to Acids, Alkalis, etc	Excellent	Excellent
Application Temperature Range	41 to 95°F	5 to 35°C
Service Temperature Range	-4 to 176°F	-20 to 80°C
Thickness	0.08"	2 mm
Width	2"	50 mm
Roll Length	33'	10 m
Core Size	3"	76 mm
Packaging — 12 rolls per case		
Denso Primer D:		
Drying Time	10 minutes	10 minutes
Flash Point	73°F	23°C
Coverage	0.26 Gal/492'	1 Liter/150 Meters
Packaging	1.3 Gallons	5 Liter can



DENSO NORTH AMERICA

HOUSTON:
9710 Telge Road,
Houston, Texas,
U.S.A. 77095
Tel: 281-821-3355
Fax: 281-821-0304

TORONTO:
90 Ironside Crescent,
Unit 12, Toronto,
Ontario, Canada M1X1M3
Tel: 416-291-3435
Fax: 416-291-0898

www.densona.com

A Member of Winn & Coales International

The information given on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be assumed.