

Hot Asphalt Joint Sealing Compound

Application Instructions

Do not apply DensoBand to wet or oil contaminated surfaces.

- a. Asphalt, concrete, stone surfaces - Clean with a stiff broom or wire brush to remove all dust, dirt and debris.
- b. Metal surfaces such as road castings and rail tracks - Wire brush to remove all loose rust, dirt, etc.

Cleaning



Diagram 1

Apply Denso Primer D™ to the vertical joint face and allow to dry.

Priming




Diagram 2

- a. Cut DensoBand to length.
- b. Remove release paper.
- c. Heat one surface of the DensoBand with a gas torch.

Applying DensoBand




Diagram 3

After laying and leveling the new wearing course asphalt, the first pass of the roller should be along the joint edges, compacting the DensoBand to form a "rivet head".

Compaction




Diagram 4



DensoBand is a polymer modified bitumen strip used for sealing joints in hot asphalt surfaces between asphalt, concrete and steel. It is also used for new road construction and maintenance, as well as bridge repair, parking lot, railway and airport runway applications.

Features / Benefits:

- Uniform, watertight, flexible seal
- Minimum maintenance
- High adhesion strength, high durability
- Withstands asphalt movement & thermal expansion
- Prevents cracking and propagation
- Hand or machine applied



DENSO NORTH AMERICA

HOUSTON:
9710 Telge Road,
Houston, Texas,
U.S.A. 77095
Tel: 281-821-3355
Fax: 281-821-0304

TORONTO:
90 Ironside Crescent,
Unit 12, Toronto,
Ontario, Canada M1X1M3
Tel: 416-291-3435
Fax: 416-291-0898

www.densona.com

A Member of Winn & Coales International